

Techni-Lux




Flexi-Par

Features

- High Impact Aluminum case design
- Unique Exclusive Prism design reflector for higher output
- Accessory holder with 2 slots and locking retaining latch.
- Interchangeable lenses make it simple to change beam field and angels
- Low Friction High Temp. Rotating lense Ring for Beam adjustment
- 360° Rotating Ring for beam shaping on wider lenses
- Attractive case design great for architectural settings
- G9.5 medium two-pin lampholder accepts a wide variety of non-proprietary Lamps.
- Heavy duty mounting Yoke with clutch
- Available in Black and White

Specifications

- 4 lenses from Very narrow to wide flood included
- Gel frame with safety glass break grid included: size 7.5"x7.5"
- 36" teflon Wire leads in High Temp cloth sheath (No Plug)
- Lamp Not included
- Dimensions: 11.5"x8.5"x8.5" (292x216x216mm)
- Weight: 7lbs (3.2kg)
- Power: 120V/60HZ
- Lense removal tool
- Approvals: ETL, CE,  listed

Included Lens

Lamp Source option G9.5 base lamp comparison. (Other lamps may be used with modification. May void Warranty)

Lamp Designation	Wattage	Voltage	Total Lumens (lm)	Color Temperature (K)	Average Life (hr)	Burn Position	Base Type	Filament Type
HX-401	400	120	8500	3050	1500	Any	Med. 2-pin G9.5	CC-8
HX-400	400	120	10000	3200	300	Any	Med. 2-pin G9.5	CC-8
EHD	500	120	10600	3000	2000	Any	Med. 2-pin G9.5	CC-8
HX-603	575	115	12000	3000	1500	Any	Med. 2-pin G9.5	4-CB
EHC/EHB	500	120	12700	3150	300	Any	Med. 2-pin G9.5	CC-8
HX-601	575	115	12800	3050	1500	Any	Med. 2-pin G9.5	CC-8
GLA***	575	115	13500	3100	1500	Any	Med. 2-pin G9.5	C-13D
EHG	750	120	15400	3000	2000	Any	Med. 2-pin G9.5	CC-8
GLC***	575	115	15500	3200	400	Any	Med. 2-pin G9.5	C-13D
HP-600	600	115	15600	3200	300	Any	Med. 2-pin G9.5	C-13D
FLK/HX-600	575	115	16500	3200	300	Any	Med. 2-pin G9.5	CC-8
HX-602	575	120	16500	3200	300	Any	Med. 2-pin G9.5	4-CB
HX-801	800	115	18000	3050	1500	Any	Med. 2-pin G9.5	CC-8
EHF	750	120	20400	3200	300	Any	Med. 2-pin G9.5	CC-8
HX-800	800	115	22000	3200	300	Any	Med. 2-pin G9.5	CC-8



Narrow Lens



Wide Lens



Very Narrow Lens



Medium Lens

TR-4583 Floor Base 9.65"



Recommended Connectors and Accessories(not Included)

- PA-FLEXIBARN/B 4 Leaf Bardoor for Flexipar - Black
- PA-FLEXIPARTOOL Lens Removal Tool for Flexipar
- TR-4583 Floor Base - Aluminum 9.65" diameter
- UG-XXX Ultra-Gel Sheets - 21" x 24" - over 250 colors Double coated Hi temp polycarbonate
- CLAMP-CLAWMINI/P Mini-Claw medium duty light clamp for 2" pipe (Will not dent trussing)
- CO-515M Edison 5266 15a 125v Male Black
- CO-STAGE3MBK Bates Stage 3-Pin Inline Male Black
- CO-L515M Twistlock 4720 15a 125v Male Black

Techni-Lux 10779 Satellite Blvd Orlando, FL. 32837

Techni-Lux reserves the right to change and improve products without notification.